

ActiV Conventional Hi-Output 100dB(A) Wall Sounder (shallow base)

Part No. BF430C/CC/SR



Overview

LPCB certified to EN54-3 (Sounders).

Impressive 100dB(A) sound output @ 1m.

31 selectable primary and secondary tone pairs and two volume levels (high and low)

Alarm Current at 30Vdc = 5.5mA.

Alarm Current at 18Vdc = 3.8mA.

IP21C rated.

Manufactured in the UK by C-TEC.

Technical Specifications

Approvals/certifications Certified to EN54-3 & 23 by the LPCB.

Compatible with C-TEC's CFP, FP, MFP and EP203 conventional fire alarm panels and virtually all Protocol/compatibility

other makes (testing on third-party panels is recommended before use)

Application/operation Designed to be wall mounted. Indoor areas only.

N/A VAD category & coverage N/A Flash rate & colour

18 to 30V DC. Supply/operating voltage Nominal SPL (Sound Pressure Level) 100dB(A).

At 30Vdc: 5.5mA; At 18Vdc: 3.8mA. Alarm current Product dimensions (mm) 108mm diameter x 99mm deep.

IP21C (Type A). IP Rating

Weight 215g.

-10°C to +55°C. Max. 95% RH (Non-condensing). Operating conditions/temperature



T 01942 322744

E sales@c-tec.co.uk

F 01942 829867

































