DATA SHEET

COD. 3348M

IKALL METAL CODED ACCESS MODULE

Digital electronic key module with LED keypad backlighting. Blue, white and off lighting options; stainless steel finish. When a number with between 1 and 8 digits is entered on the keypad, two relays (10A) are activated, allowing electric door locks or other devices to be operated. 12 V AC/DC power supply. Dimensions 112x89.5x40 mm.



General specifications

Backlighting colour:	LED BLUE / WHITE / OFF
Baokinghang boloar.	

Hardware specifications

Vandal Resistant IK:	No	
Customisable housing:	No	
DDE function:	No	
Total buttons:	12	
Sensitive Touch technology:	Yes	

Functions

Key bu	Itton function:	Yes

General info

Product height (mm):	89,5
Product width (mm):	112
Product depth (mm):	40
Operating temperature (°C):	-25/55
Intrastat code:	8517709000

Compatibility

Access Control Family:	Yes	
Simplebus Top system:	Yes	
Simplebus Color system:	Yes	
Simplebus 2 system:	Yes	
Vip system:	Yes	
Traditional system:	Yes	



The technical specifications are subject to variations without warning

/		
Mounting/Installation		
Flush-mounted:	Yes	
Wall-mounted:	Yes	
Audio/video specifications		
Audio system:	Yes	
Audio/video system:	Yes	
Electrical specifications		
Maximum current absorption (mA):	200	
Packaging		
Single pack height (mm):	55	
Single pack width (mm):	110	
Single pack weight (Kg):	0,334	
Single pack depth (mm):	95	
Single pack volume (dm3):	0,575	

