# **DATA SHEET**

# COD. 4680C

#### **IKALL SIMPLEBUS COLOUR CAMERA**

Simplebus Color system audio/video unit with terminal block complete with front-adjustable wide-angle 1/4? colour camera and LED camera illumination. Complete with terminal block and digital audio management system with Eco-cancelling, watertight loudspeaker and electrets microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. Audiovisual indications for disabled individuals assistance request can be activated via programming. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lock-release function (3A), plus C, NC, NO contacts for 10A relay. For use in modules Art. 33410, 33411 and 33412. Dimensions: 102x55x38 mm. Compatible with all SBTOP functions and products. Allows call addressing for up to 120000 users. Timed lock-release input and door open indication.



# **General specifications**

Signal/noise ratio (dB):	48
Video output:	1 / 75 PAI

## Software/firmware specifications

Video resolution (H x V):	500x582	

#### **Hardware specifications**

DDE function:	SI

#### **Functions**

Key button function:	SI
Loudspeaker volume control:	SI
Microphone volume control:	SI

### General info

Product height (mm):	55
Product width (mm):	104
Product depth (mm):	35
Operating temperature (°C):	-25/55
EAN product code:	8023903209174
Intrastat code:	85176910
S/N ratio dB:	48

#### Compatibility

Simplebus Top system:	SI
Simplebus Color system:	SI



# **DATA SHEET**

Simplebus 2 system:	SI
Audio/video specifications	
Type of sensor:	1/4" CCD
Horizontal resolution (TVL):	420
Audio system:	No
Audio/video system:	SI
Technical properties	
Sensitivity (lux):	1
Type of camera:	COLOR
Electrical specifications	
Maximum current absorption (mA):	400
Packaging	
Single pack height (mm):	53
Single pack width (mm):	110
Single pack weight (Kg):	0,223
Single pack depth (mm):	94
Single pack volume (dm3):	0,548

