

4682HD





ViP system audio-video unit with terminal block, complete with colour camera. Resolution 1280x720 pixels. Recording angle 110° (H) - 80° (V). IR led camera lighting. Complete with terminal block and digital audio management system with Echo-cancelling, watertight loudspeaker and electrets microphone; loudspeaker volume can be adjusted from the front. Programmable audio visual functions for users with disabilities. Standard POE audio-video unit, but if necessary 33 VDC power supply can be used the power supply unit art. 1595. Compatible with H.264 video format. Dimensions: 102x55x38 mm.



4682HD

HD COLOUR AUDIO/VIDEO UNIT, IKALL SERIES. VIP

MAIN FEATURES	
Audio/video system:	Yes
Output for induction loop module:	Yes
Camera:	Color
Diagonal viewing angle (°):	125
Video encoding:	H.264
Lens size (inch):	2.8
Power supply voltage:	30 ÷ 57
Clamps:	TX- TX+RX- RX+V- V+RTE GND SE COM NC NO
Microphone:	Yes
Microphone volume control:	Yes
Loudspeaker:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°F):	-31 ÷ 131
Signal/noise ratio (dB):	40

FUNCTIONS		
Key button function:	Vos	

HARDWARE SPECIFICATIONS	
Visual signalling:	Yes
Acoustic signalling:	Yes
Speech synthesis:	Yes

SETTINGS	
Loudspeaker volume control:	Yes
Microphone volume control:	Yes

GENERAL DATA	
Height (inch):	2.17
Width (inch):	4.02
Depth (inch):	1.5

COMPATIBILITY	
Vip system:	Yes

CONNECTIVITY	
Ethernet ports:	1



4682HD

HD COLOUR AUDIO/VIDEO UNIT, IKALL SERIES. VIP

ELECTRICAL SPECIFICATIONS	
Door release (dry contact bridge):	Yes
Door release (direct current output):	Yes