

SIMPLEBUS COLOUR SYSTEM POWER SUPPLY MIXER

The mixer is contained in a 8 DIN module box. Supplied from 110V mains, it has a dedicated output for power supply switching device art. 1224A. On input it receives a Simplebus 1 type signal and superimposes the monitor power supply for the riser. Up to 100 pieces of apparatus between telephones and monitors can be connected, distributed over 4 outputs. Fitted with LED which signals any shortcircuits on the lines. Fitted with 4 terminals for line termination art. 1216. Dimensions: 140X140X67 mm (8 DIN modules). From the RI013 it is compatible with all SBTOP functions and products. Allows management of alarm signals and direct intercommunication between users without the aid of an interface or porter switchboard, It allows call addressing for up to 120000 users. It should be stressed that the mixer is not compatible with the TOP system when main and secondary switchboards are used in the same system, when the intercom function without interface is present and active and when the alarm function is being managed on the system.



Compatibility

Simplebus Top system:	Yes
Simplebus Color system:	Yes

Mounting/Installation

Wall-mounted:	Yes
Surface-mounted:	Yes
DIN rail mounted:	Yes
DIN modules (no.):	8

Audio/video specifications

Audio system:	Yes
Audio/video system:	Yes

Technical properties

Temperature range:	0 / 40
--------------------	--------

Electrical specifications

AC supply voltage:	230 V
Maximum current absorption (mA):	700

General info

EAN product code:	8023903178241
Product height (mm):	105
Product width (mm):	140
Product depth (mm):	51,5

Packaging

Single pack height (mm):	106
--------------------------	-----

DATA SHEET

Single pack width (mm):	338
Single pack weight (g):	680
Single pack depth (mm):	159