

DHI-LM50-F400N

Dahua 50" UHD LED Monitor



Series Overview

The Dahua F400N Series monitor comes with a stunning 4K high definition panel and is engineered to deliver exceptional performance 24/7. With its sleek plastic shell and elegant 3-side narrow frame design, it is visually appealing. Furthermore, it seamlessly integrates with various Dahua backend security devices, making it an ideal choice for both desktop and wall mount installation in the security industry.

Technical Specification

Display

2.56.47		
Model	DHI-LM50-F400N	
LCD Technology	IPS	
Backlight	DLED	
Screen Size	50 inch	
Aspect Ratio	16:9	
Viewing Size	1095.84 (W) × 616.41 (H) mm	
Screen-to-Body Ratio	≥95%	
Viewing Angle	178° (H) / 178° (V)	
Display Mode	Horizontal	
Pixel Pitch	0.285 mm × 0.285 mm	
Pixels Per Inch	89	
Resolution	3840 (H) × 2160 (V)	
Refresh Rate	60 Hz	
Display Color	8 bit + FRC	
Color Gamut	72% NTSC	
Brightness	400 cd/m² (typ.)	
Contrast Ratio	1200:1	

- 4K Ultra-HD resolution
- IPS panel, suitable for continuous 24/7 operation
- · Ultra-narrow bezel design, elegant appearance
- 178°H/178°V extra-wide viewing angle for overall viewing performance
- · High fidelity digital processing for a brilliant and vivid video
- · 8ms response time for no motion blur, judder or ghosting
- · Support multiple signal interfaces including HDMI, VGA, USB, etc.
- Built-in speaker













Response Time	8 ms
Lifespan	30000 hrs
Surface Treatment	Haze 25%, 3H
Flicker-free Technology	Yes
Low Blue Light	Software blue light protection

Device Ports

Input Port	2 × HDMI 2.0 (3840 × 2160@60 Hz), 1 × VGA (1920 × 1080@60 Hz), 2 × USB 2.0, 1 × Audio in, 1 × RS-232 in
Output Port	1 × Audio out
Speaker	2 × 10 W

Power & Environmental Conditions

Power Supply	100–240 VAC (±10%), 50/60 Hz	
Power Type	Built-in Power	
Power Consumption	64 W (basic), 89 W (typ.), 94 W (max)	
Standby Power Consumption	<0.5 W	
Operating Temperature	0 °C to +40 °C (+32 °F to +104 °F)	
Operating Humidity	10%-85% (RH)	
Storage Temperature	-20 °C to +60 °C (-4 °F to +140 °F)	
Storage Humidity	5%-90% (RH)	

General

Product Dimensions	1,110.6 mm × 641.0 mm × 81.7 mm (43.73" × 25.24" × 3.22") (W × H × D), without base	
Package Size	1,190 mm × 750 mm × 125 mm (46.85" × 29.53" × 4.92") (W × H × D)	
Frame Width	U/L/R/D: 1.1 mm/1.1 mm/1.1 mm/15.3 mm	
Net Weight	8.60 kg (18.96 lb)	

F400N Series | DHI-LM50-F400N

Gross Weight	11.60 kg (25.57 lb)	
Casing Color	Black	
Control Mode	Remote Control, RS-232	
Status Indicator Light	Yes	
Wall Mount VESA	200 mm × 300 mm (7.87" × 11.81")	
Accessory	Power cord, base, HDMI cable, remote control, user's manual, legal and regulatory information etc.	
Optional Accessory	Wall mount	
Certification		
Certifications	CE EMC, CE LVD, CE ERP	

Ordering Information				
Туре	Model	Description		
LED Monitor	DHI-LM50-F400N	Dahua 50" UHD LED Monitor		

Dimensions (mm[inch])

