



2N® Helios IP Verso

Modular IP Intercom



IP INTERCOMS

www.2n.cz



VERTICALS



Office



Residential



Education



Healthcare



Government



Leisure & entertainment

Ready to meet all requirements

- Choose your configuration of the required number of buttons, extending modules like Display Touch screen, Bluetooth and many others.

All used components and materials are industry grade and will provide excellent performance in any conditions.





Bright picture even at night

- Hidden integrated camera is producing sharp image with HD resolution and night vision so you will see all visitors clearly even in a dark night.

Never Miss a Word

- High output power integrated amplifier together with HD audio codec will provide you crystal clear sound output with great intelligibility.

Full duplex sound processing ensures that you will always hear your visitor even in loud environments.






Integration

- > An integration with other security systems in the building brings an extra value and security. It works with open standards like ONVIF, HTTP based APIs and modern streaming features to integrate with video surveillance, burglar alarms or home automation systems.

CONNECTION TOPOLOGY



INTEGRATION WITH 3RD PARTY PRODUCTS



TELEPHONY

Cisco
Avaya
Alcatel-Lucent
Fritz
Skype
Gigaset
Asterisk
Yealink
Wildix



ACCESS CONTROL

Wiegand



VIDEO MANAGEMENT SYSTEMS

Milestone
Axis Communications
Genetec
DigiFort
Axxon
Onvif
See Tec
Aimetis
Digivod
Netavis



HOME AUTOMATION

Control4
Savant
Fibaro

PRODUCT VARIANTS – MAIN UNITS



Main unit with camera

9155101C



Main unit without camera

9155101

PRODUCT VARIANTS - MODULES



Bluetooth

9155046



Touch Display

9155036



RFID card reader
125kHz

9155032



RFID card reader
13,56MHz NFC

9155040



Secured RFID card
reader 13,56MHz

9155042

PRODUCT VARIANTS - MODULES



Keypad

9155031



5 Buttons

9155035



Infopanel

9155030



Induction
loop

9155041



Blanking

9155039

PRODUCT VARIANTS - MODULES



I/O

9155034



Wiegand


9155037



Tamper switch

9155038

MODULARITY



Technical Specification

- **Signalling protocol:** SIP 2.0 (RFC - 3261)
- **Microphone:** 1 built-in microphone, Speaker 2W
- **Camera (optional) Resolution:** JPEG 1280 x 960px – video call 640 x 480px
- **Viewing angle** 120° (H), 90° (V), 145° (D)
- **Night vision:** Yes Automatic IR cut filter and IR light
- **Video stream:** Codecs H.263+, H.263, H.264, MJPEG, MPEG-4
- **Power supply:** 12V ± 15%/ 2A DC, or PoE 802.3af (Class 0 - 12.95W)



IK8



IP54

ANTI
VANDAL